


1RU Ready HMI Engine

19" half Rack Ready

Product Specification

Customer	Standard		
Product Number	DMT066YYHLCMU-1D		
Customer Part Number			
Customer Approval		Date:	

Internal Approvals

Product Mgr	Doc. Control	Electr. Eng.
Bazile Peter	Kadafi Ali	Filip Kaczorowski
Date: 2019/03/30	Date: 2019/03/27	Date: 2019/03/23

Revision Record

Rev.	Date	Page	Chapt.	Comment	ECR no.
A	2019-03-27	--	--	Preliminary	

Table of Contents

1.0 GENERAL DESCRIPTIONS	4
1.1 Introduction	4
1.2 Main Features	4
1.3 Scanning Frequency	5
1.4 Input Resolution [USB]	5
1.5 Input/Output Signal	5
1.6 User Controls	5
1.7 Key Button Function	6
2.0 MECHANICAL SPECIFICATION	7
2.1 Mechanical Characteristics	7
2.2 Mechanical Drawing	8
2.3 Product picture	9
2.4 Block Diagram	10
3.0 ELECTRICAL SPECIFICATION	11
3.1 Power consumption	11
4.0 TIMING AND OPERATING SYSTEMS	12
4.1 Timing characteristics	12
4.2 Operating systems	12
5.0 OPTICAL SPECIFICATION	13
5.1 Optical Characteristics	13
6.0 ENVIRONMENTAL SPECIFICATION	13
6.1 Environmental Characteristics	13

1.0 General Descriptions

1.1 Introduction

This industrial TFT-LCD monitor is a high performance TFT LCD monitor for rack mount products and provides a high image from the USB B Type Interface.

1.2 Main Features

Item	Contents
Screen Size	6.6" Diagonal
Display Format	1440(H) x RGB x 240 (V) dots
Colour	16.7M
Overall Dimensions	230 (W) × 44.0 (H) × 23.2 (D) mm
Active Area	164.16 mm (H) x 27.36 mm (V)
Pixel Pitch	0.114 (H) x 0.114 (V)
Viewing Angle	L/R: 160°(Typ.) U/D: 160° (Typ.)
Contrast Ratio	800: 1 (Typ.)
Brightness	750 CD/m2
I/O	3 x USB (B Type)
Backlight	LED
Mechanism	Durable Metal Case
Plug & Play	USB DisplayLink
Response time	25 msec
Touch Panel	PCT
Touch Interface	USB
Operating temperature	-10°C ~ +60°C
Storage temperature	-10°C ~ +60°C